



DEF TRANSFER HOSE

Heavy Duty Diesel Exhaust (DEF) Hose

Heavy duty suction/discharge hose specifically designed for transferring DEF (Diesel Exhaust Fluid) in truck delivery and tank applications. The inner tube is constructed from peroxide cured EPDM synthetic rubber and tested/certified to ISO-22241.



DEF  HEAVY DUTY

TECHNICAL DATA

Tube	EPDM, peroxide cured, does not interfere with purity of AdBlue
Reinforcement	High tensile textile cord, steel helix
Cover	EPDM, blue, smooth, weather and abrasion resistant
Temperature	-22°F to +212°F (-30°C to +100°C)



	#						
I.D.	Part Number	O.D.	Std. Length	Working Pressure (psi)	Vacuum (in./HG)	Bend Radius	Lbs./Ft.
3/4"	DEF-.75-100	1-11/64"	100'	150	29	3"	0.41
1"	DEF-1.0-100	1-27/64"	100'	150	29	4"	0.52
1-1/4"	DEF-1.25-100	1-44/64"	100'	150	29	5"	0.63
1-1/2"	DEF-1.5-100	1-60/64"	100'	150	29	6"	0.75
2"	DEF-2.0-100	2-30/64"	100'	150	29	8"	1.10
2-1/2"	DEF-2.5-100	2-63/64"	100'	150	29	10"	1.44
3"	DEF-3.0-100	3-35/64"	100'	150	29	12"	1.85
4"	DEF-4.0-100	4-39/64"	100'	150	29	16"	2.73