



GAMMA™-FLEX TANK

Corrugated Tank Truck Hose

A world-class hose for tank truck, in-plant and oilfield loading operations requiring a strong yet flexible hose. Dramatic flexibility (one-to-one ratio, up to 4" inside diameter) for ease of handling.



TECHNICAL DATA

Tube	Black, Nitrile, 55% aromatics (ORS)
Cover	Black, Neoprene (corrugated)
Reinforcement	High tensile tire cord plies; dual helix wire
Safety Factor	4:1
Temperature	-40°F to +180°F
Branding	TEXCEL® GAMMA™-FLEX TANK - FLEXIBLE TANK TRUCK HOSE 150 PSI W.P.
Features	Exceptional flexibility



 I.D.	 Part Number	 O.D.	 Std. Length	 Working Pressure (psi)	 Vacuum (in./HG)	 Bend Radius	 Lbs./Ft.
1-½"	GTA15F1-1.5	1- ⁶³ / ₆₄ "	100'/200'	150	29	3.5"	0.77
2"	GTA15F1-2.0	2- ³⁰ / ₆₄ "	100'/200'	150	29	4.5"	1.02
2-½"	GTA15F1-2.5	3"	100'/200'	150	29	5.5"	1.31
3"	GTA15F1-3.0	3- ³² / ₆₄ "	100'/200'	150	29	7"	1.60
4"	GTA15F1-4.0	4- ³⁶ / ₆₄ "	100'/200'	150	29	9"	2.55
5"	GTA15F1-5.0	5- ⁴⁶ / ₆₄ "	100'	150	29	14"	3.86
6"	GTA15F1-6.0	6- ⁴⁸ / ₆₄ "	100'	150	29	19"	4.17
8"	GTA15F1-8.0	8- ⁵² / ₆₄ "	100'	150	29	30"	6.02