



Chemflex - Rubber Covered PTFE

Rubber hoses



← PREVIOUS



Product Spec

Characteristics

Description: A flexible, blue EPDM rubber hose with a Khemgard® FEP tube. The helix wire construction allows for full vacuum service.
Applications: Chemical transfer, pharmaceuticals, food & beverage; cosmetics
Temperature Range: -40°F to +300°F (-40°C to +149°C) Continuous

Construction

Tube: FDA compliant Khemgard® FEP
Reinforcement: High tensile synthetic plies with an embedded helix wire
Cover: Blue, ozone and weather resistant. Superior resistance to abrasion
Available upon request: Private branding and optional cover colors. Please contact MTD for more information.

Code	I.D. (in)	O.D. (in)	Working Pressure (PSI)	Burst Pressure (PSI)	Vacuum (Hg)	Bend Radius (in)	Weight (lbs/ft)	Add to Cart
RCT-08	1/2	0.87	550	2200	29.9	2.95	0.33	Request For Quote
RCT-12	3/4	1.22	500	2000	29.9	3.54	0.54	Request For Quote
RCT-16	1	1.46	450	1800	29.9	4.72	0.64	Request For Quote
RCT-20	1.1/4	1.73	400	1600	29.9	5.91	0.81	Request For Quote
RCT-24	1.1/2	2.05	350	1400	29.9	7.09	1.01	Request For Quote
RCT-32	2	2.56	300	1200	29.9	9.06	1.48	Request For Quote
RCT-40	2.1/2	3.11	250	1000	29.9	13.65	2.02	Request For Quote
RCT-48	3	3.62	200	800	29.9	16.93	2.49	Request For Quote
RCT-64	4	4.8	150	600	29.9	22.83	3.29	Request For Quote

← PREVIOUS

