

TEX-AQUA HD

Heavy-Duty Water Suction & Discharge Hose

Constructed with the highest quality compounds to provide maximum flexibility, long life and lighter weight for easy handling.



TECHNICAL DATA

Tube	Black, SBR/EPDM blend
Cover	Black, SBR/EPDM blend
Reinforcement	High tensile tire cord plies; helix wire
Safety Factor	3:1
Temperature	-40°F to +180°F
Ends	Soft cuffs available on 6" and 8" sizes only
Branding	TEXCEL® TEX-AQUA HD - HEAVY DUTY WATER SUCTION & DISCHARGE HOSE XXX PSI W.P.
Note	6" and 8" available in a smooth or corrugated cover For extra flexibility use 5"-12" corrugated



SMOOTH COVER

	#						
I.D.	Part Number	O.D.	Std. Length	Working Pressure (psi)	Vacuum (in./HG)	Bend Radius	Lbs./Ft.
1"	AQUA-HD-1.0	1-19/64"	100'	150	29	4"	0.50
1-1/4"	AQUA-HD-1.25	1-49/64"	100'	150	29	5"	0.62
1-1/2"	AQUA-HD-1.5	1-59/64"	100'	150	29	7"	0.85
2"	AQUA-HD-2.0	2-29/64"	100'/200'	150	29	10"	1.06
2-1/2"	AQUA-HD-2.5	2-59/64"	100'	150	29	11"	1.31
3"	AQUA-HD-3.0	3-29/64"	100'/200'	150	29	12"	1.73
4"	AQUA-HD-4.0	4-32/64"	100'/200'	150	29	14"	2.55
6"	AQUA-HD-S-6.0	6-49/64"	20'/100'	150	25	19"	5.90
8"	AQUA-HD-S-8.0	8-49/64"	20'/100'	150	25	20"	7.90

CORRUGATED COVER

	#						
I.D.	Part Number	O.D.	Std. Length	Working Pressure (psi)	Vacuum (in./HG)	Bend Radius	Lbs./Ft.
5"	AQUA-HD-5.0	5-41/64"	100'	150	25	14"	4.50
6"	AQUA-HD-6.0	6-44/64"	20'/100'	150	25	15"	5.50
8"	AQUA-HD-8.0	8-48/64"	20'/100'	150	25	16"	7.50
10"	AQUA-HD-10.0	10-48/64"	20'/25'	100	20	18"	10.00
12"	AQUA-HD-12.0	12-56/64"	20'/25'	100	20	20"	12.00