



TEX-BLAST

Premium Plus Grade Sandblast Hose

Our premium plus grade sandblast hose is engineered with a thick, static-dissipating natural rubber tube that delivers exceptional abrasion resistance, tested to exceed $<40 \text{ mm}^3$ DIN abrasion loss. This hose is designed for heavy-duty blasting applications, including steel shot, garnet, aluminum oxide, and other aggressive media. Ideal for high-pressure, high-cycle environments, it provides extended service life in industrial surface preparation, shipyards, foundries, and construction settings where durability and performance are critical.



TEX-BLAST



TECHNICAL DATA

Tube	Black, SBR/GUM, wear-resistant, static-dissipating materials. According to DIN 53516 $\leq 40 \text{ mm}^3$
Cover	Black, SBR (pinpricked)
Reinforcement	High tensile tire cord plies
Safety Factor	4:1
Temperature	-40°F to +190°F
Branding	TEXCEL® TEX-BLAST - PREMIUM GRADE SANDBLAST HOSE 150 PSI W.P.

	#					
I.D.	Part Number	O.D.	Std. Length	Working Pressure (psi)	Fabric Plies	Lbs./Ft.
1/2"	BLAST-.50	1-8/64"	50'	150	2	0.40
3/4"	BLAST-.75	1-32/64"	50'	150	4	0.57
1"	BLAST-1.0	1-56/64"	50'	150	4	0.94
1-1/4"	BLAST-1.25	2-8/64"	50'	150	4	1.18
1-1/2"	BLAST-1.50	2-24/64"	50'/100'	150	4	1.35