



TEX-FLO 2MD

Medium-Duty 2-Ply Water Discharge Hose

Soft-wall design gives similar performance to a lay-flat hose, but with increased abrasion resistance and tensile strength.



TECHNICAL DATA

Tube	Black, SBR/EPDM blend	
Cover	Black, SBR/EPDM blend	
Reinforcement	High tensile tire cord plies	
Safety Factor	3:1	
Temperature	-40°F to +180°F	
Branding	TEXCEL® TEX-FLO 2MD - WATER DISCHARGE HOSE 2PLY XXX PSI WP	

	#					
I.D.	Part Number	O.D.	Std. Length	Fabric Plies	Working Pressure (psi)	Lbs./Ft.
1-1/2"	FLO-2MD-1.5	1-52/64"	100'	2	150	0.41
2"	FLO-2MD-2.0	2-20/64"	100'	2	150	0.52
2-1/2"	FLO-2MD-2.5	2-52/64"	100'	2	150	0.65
3"	FLO-2MD-3.0	3-20/64"	100'	2	150	0.77
4"	FLO-2MD-4.0	4-20/64"	100'	2	150	1.06
6"	FLO-2MD-6.0	6-22/64"	100'	2	150	1.88
6-5/8"	FLO-2MD-6.625	7-5/64"	100'	2	100	2.18
8"	FLO-2MD-8.0	8-23/64"	100'	2	100	2.61
10"	FLO-2MD-10.0	10-27/64"	100'	2	80	3.47