


TEX-PUSH-ON 300

300psi Push-On Hose

Low pressure braided hose for quick and easy insertion of push-on fittings with no special crimping tools required. Its internal polyester reinforcement design allows for excellent coupling retention. Tube handles oil-laden air, lubricating oils, mild alkalis or caustic solutions, fuel oil, and other petroleum-based products.



TECHNICAL DATA

Tube	Black, NBR (ARPM Class A)
Cover	Black, Red, Blue NBR/PVC (ARPM Class A)
Reinforcement	Reinforced braided polyester cords
Safety Factor	4:1
Temperature	-40°F to +212°F (-40°C to +100°C)
Branding	TEXCEL® TEX-PUSH-ON <ID>
Packaging	1pc Reel

			#								
Dash	I.D. Inch	Dn	Part Number	Inch	mm	psi	bar	psi	bar	lbs/ft	Kg/mt
4	1/4	6	PUSH-4-250*	1/2	13	300	21	1200	83	0.10	0.15
5	5/16	8	PUSH-5-250*	14/25	14.33	300	21	1200	83	0.12	0.18
6	3/8	10	PUSH-6-250*	33/50	17	300	21	1200	83	0.14	0.20
8	1/2	12	PUSH-8-250*	81/100	21	300	21	1200	83	0.19	0.28
10	5/8	16	PUSH-10-250*	47/50	24	300	21	1200	83	0.22	0.33
12	3/4"	19	PUSH-12-250*	1-9/100	28	300	21	1200	83	0.28	0.43
16	1	25	PUSH-16-250*	1-2/5	35.5	250	17	1000	69	0.46	0.68

* For color variations of Blue, Red or Gray, add color name to the end of the part number, for example: PUSH-4-250-RED. Note: PUSH-5-250-BLUE is only available in Blue Cover.